



Absolute safety, today










■ CHARGING SOCKETS AND TERMINALS FOR ELECTRIC VEHICLES

The Green'Up Access 2P+E socket with safety shutters charges your vehicle safely in mode 1 and mode 2 safer than with a conventional socket



Used for safely charging rechargeable electric and hybrid vehicles which take mode 2 cord (compatible with mode 1)
Connected to the consumer panel via one 3 x 2.5 mm² dedicated line (1 line per socket) protected by 30 mA - 20 A C curve, type A or HPI RCBO (or 30 mA type A or HPI RCCB + 20 A C curve circuit breaker)
Recommended installation height: 1.30 m from the ground
Suitable for residential and workplace use

Pack	Cat.Nos	Mode 1 and mode 2 sockets - 3.2 kVA
		Heavy-duty mechanisms with silvered contacts Single-phase sockets - screw connection - 230 V Supplied with base Cat.No 0 904 78 for hanging up the vehicle charging cable control box For charging 1 vehicle Conform to IEC 60-884-1
		IP 66 - IK 08 surface-mounting Suitable for installation in private houses Plastic socket with flap cover Supplied complete with surface mounting box fitted with an ISO 20 cable gland Dimensions (H x W x D): 98 x 98 x 70 mm (exc. cable gland)
1	0 904 72	 German standard socket outlet  British standard socket outlet  French standard socket outlet
1	0 904 73	
1	0 904 71	
		IP 55 - IK 10 flush-mounting - metal socket Suitable for installation in private houses, lock-up garages, parking lots, etc Supplied complete with plate and support Mounting in 1-gang Batibox flush-mounting box depth 50 mm Can be surface mounted with box Cat.No 0 778 90 Dimensions (H x W x D): 110 x 110 x 13.5 mm
1	N 0 778 97	 French standard socket outlet  German standard socket outlet
1	0 778 56	
		IP 55 - IK 10 flush-mounting - metal socket with locked flap cover Suitable for installation in private houses, lock-up garages, parking lots, etc Supplied complete with plate and support Mounting in 1-gang Batibox flush-mounting box depth 50 mm Can be surface mounted with box Cat.No 0 778 90 Dimensions (H x W x D): 110 x 110 x 13.5 mm Supplied complete with a unique set of 2 keys in order to restrict access to the socket
1	N 0 778 98	 French standard socket outlet  German standard socket outlet
1	0 778 57	
1	0 904 78	Base For hanging up the vehicle charging cable control box Plastic