



Saves Your Energy

PRODUCT CARD

19.8.2015

KA460.12

Name: **Terminal block 460.12-AK**


12-pole

Type: KA460.12

GTIN: 6418677104701

Description: Terminal block with flat base. Mounting hole Ø 4.2 mm. Terminal screw M 3.5. Terminal block can be ordered pre-cut to desired number of poles.

On request individual pole positions can be marked with desired markings. To order imprinting please specify the characters on your order. Turret or ledge marking available.



Package: 250/11250

Unit: PCS



Technical specification

Electrical values

CSA	460-12
CSA Rated current	40 A
CSA Rated voltage	300 V
CSA Wire range	18-10 AWG

Ratings

Rated voltage	450 V
---------------	-------

Mechanical

Tightening torque	0.79 Nm
-------------------	---------

Dimensions

Dimensions l x w x h	140x23,2x17,7
Conductor cross-section	6 mm ²
Diameter of mounting hole	4.2 mm

Temperatures

Max. operating temperature	+100 °C
----------------------------	---------

Features

Number of poles	12
-----------------	----

Materials

Material	Polyamide 6
----------	-------------

Certificates

UL File no.	E103245
-------------	---------

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2750

www.ensto.com