Product data sheet Characteristics

NSYMM88

Plain mounting plate H800xW800mm made of galvanised sheet steel





Main

Main Range Accessory / separate part category Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description Range compatibility	Spacial Mounting accessory Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D Spacial S3D Spacial S3X
Range Accessory / separate part category Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description	Mounting accessory Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Range Accessory / separate part category Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description	Mounting accessory Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Range Accessory / separate part category Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description	Mounting accessory Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Accessory / separate part category Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description	Mounting accessory Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Product or component type Device application Enclosure nominal dimensions Mounting location Mounting plate description	Mounting plate Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Device application Enclosure nominal dimensions Mounting location Mounting plate description	Multi-purpose 800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Enclosure nominal dimensions Mounting location Mounting plate description	800 mm W: 800 mm Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Mounting location Mounting plate description	Step slide Direct fixing on backstuds Plain Spacial CRN Spacial S3D
Mounting plate description	Direct fixing on backstuds Plain Spacial CRN Spacial S3D
	Spacial CRN Spacial S3D
Range compatibility	Spacial S3D
	Thalassa PLM
Quantity per set	Set of 1
Material	Galvanised steel
Complementary	
Fixing mode	Screwed on backstuds - screw type M8 By fixing element
Permanent permissible load	150 kg
Height	750 mm
Width	750 mm
Depth	125 mm
Thickness	2.5 mm
Product weight	11.03 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity

Complementary

Fixing mode	Screwed on backstuds - screw type M8 By fixing element	et in the second se
Permanent permissible load	150 kg	ubsetit.
Height	750 mm	ນ ກ ນ
Width	750 mm	
Depth	125 mm	
Thickness	2.5 mm	
Product weight	11.03 kg	itio X

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity

	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period

18 months