



Saves Your Energy

PRODUCT CARD

1/6/17

KE62.3

Clampo Pro terminal

Code	KE62.3
GTIN	6418677191879
Name	Clampo Pro terminal Ensto Clampo Pro 1-pole, yellow/green, Al/Cu 16-95 mm ²
Description	Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm ² .
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Weight:	0.07 kg
Conductor cross-section:	16-95

Temperatures

Operating temperature:	≤ 80 °C
------------------------	---------

Electrical values

Pollution degree:	3
-------------------	---

Materials

Housing:	Polyamide
----------	-----------

Colors

Color:	Yellow-green
--------	--------------

Features

Number of poles:	1
Screw head:	Hexagon
Screw head size:	5 mm
Mounting:	DIN rail

Mechanical

Tightening torque:	20 Nm
--------------------	-------

Certificates

Standards:	EN 60947-7-2, IEC 61238-1, UL 1059
Connector class:	A
UL category:	XCFR2
UL File no.:	E192532, E192532

Ratings

ETIM class:	EC000897
--------------------	----------

US specific

Conductor size:	4/0-4
Tightening torque:	126 Lb-In

ETIM

ETIM

Colour:	Green/yellow
Length:	86 mm
Mounting method:	DIN rail (top hat rail) 35 mm
Nominal rated voltage:	800 V
Connectable conductor cross section fine-strand without cable end sleeve:	16 ... 70 mm ²
Connectable conductor cross section fine-strand with cable end sleeve:	16 ... 70 mm ²
Connectable conductor cross section multi-wired:	16 ... 95 mm ²
Type of electrical connection 1:	Screw connection
Connection position:	Sideways
Number of levels:	1
Number of clamp positions per level:	2
Material insulation body:	Thermoplastic
Operation temperature:	-5 ... 80 °C
Width/grid dimension:	24 mm
Height at lowest possible mounting height:	49 mm
Type of electrical connection 2:	Screw connection
Inflammability class of insulation material acc. with UL94:	V2

Packaging

Default package

Unit:	PCS
Size:	3