



Power and productivity  
for a better world™

## PRODUCT CARD

7.6.2016

# AUS74

1/2

Name: **Renovation box**

Renovation box for board walls hole 74 mm

Type: AUS74

EAN: 6438199004570

Description: The AUS74 is a front-mounted mounting box with telescope bottom part for board walls of 1 – 3 gypsum boards ( thickness of the wall 9 – 39 mm ). The height of the box is 54 – 70 mm thanks to the moving bottom part. The installation hole diameter is 73 - 74 mm (box drill AT4). At the side of the bottom part are three inlets for the 16 mm flexi pipe. There is also one inlet for the 16/20 mm and one inlet for the 20 mm flexi pipe. There are two inlets with strain reliefs on the bottom of the box for installing 8 - 13 mm cables and two inlets for the low voltage cables. Box combinations can be made both horizontal and vertical directions without any extra parts. The box has four openings, one on each side, through which conductors can also be conveyed from one box to another. At the top of the box there are two fixing places for screws to install it to the log wall. At the bottom there are marking holes for making box combinations (c/c 71 mm) . The protection class is IP3X. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

Package: 60

Unit: PCS



### ETIM

ETIM 5.0 EC002601 (EC002601)

### ETIM 5

Mounting method	Flush mounted (plaster)
Shape	Round
Construction type	Device connection box (round/square)
Model	Single
Equipped with	None
Diameter	74 mm
Depth	54 mm
Internal depth	52 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	1
For tubediameter	16 mm
Suitable for cable diameter	8 ... 13 mm

Address  
P.O. Box 16  
06101 Porvoo  
FINLAND

ABB Exchange  
+358 10 22 11

Customer service  
customerservice.ABJ@fi.abb.com

Web  
<http://www.abb.fi>

Business ID  
0763403-0



Power and productivity  
for a better world™

## PRODUCT CARD

7.6.2016

# AUS74

2/2

Pipe locking	1
Inlet from the rear	
Number of inlets	
Material	Plastic
Halogen free	1
Surface protection	Untreated
Colour	White
Degree of protection (IP)	IP3X
Cover	None
Cover attachment	Not applicable
Sealable	
Circuit integrity	None
With screening	
Wind proof	
Max. conductor cross section	0 mm <sup>2</sup>
Number of poles of the clamp	
Clamp position fixed	
Luminaire hook mounting	
Nozzle	None
With nail lugs	

Address  
P.O. Box 16  
06101 Porvoo  
FINLAND

ABB Exchange  
+358 10 22 11

Customer service  
customerservice.ABJ@fi.abb.com

Web  
<http://www.abb.fi>

Business ID  
0763403-0