PlusLink-Inserts



Side controller Plus, 1-gang



Version

Art. no.

MTN5119-6000

For System Design.

One PlusLink line with PlusLink input for triggering all devices. The device has one PlusLink

The control function via PlusLink requires a separate core in the installation to the receiving devices.

With screw terminals.

With claw and screw fixing.

Functions:

■ Line control via a PlusLink output.

Switching, dimming connected loads.
Controlling blinds/roller shutters, slat adjustment.

Nominal voltage: AC 220/230 V, 50/60 Hz

Output: 1 x PlusLink

Neutral conductor:not required (2 conductor system)

Wire range: max. 2x2.5 mm²

To be completed with: Rocker for 1-gang push-button module System Design MTN5210-

60..

Rocker for 1-gang push-button module (Up/Down) System Design MTN5215-60..

Accessories: PlusLink Expander CCTDT5130 Receiver: Electronic switch insert MTN5151-00... Electronic switch insert, 2-gang MTN5152-00.. Relay switch insert MTN5161-00..

Relay switch insert, 2-gang MTN5162-00... Universal dimmer insert MTN5171-00. Universal dimmer insert, 2-gang MTN5172-00...

Blind control insert MTN5165-0000 1-10 V insert MTN5180-00.. DALI insert MTN5185-00...

Note: All controlling functions are included in the module. An insert without a module con-

nected to it has no function.

