

DPX³ 160 thermal magnetic

MCCBs from 16 to 160 A



4 200 00

4 200 10

4 200 37

4 201 57

Electrical characteristics **see e-catalogue**
Dimensions **see e-catalogue**

Can be mounted on rail or on plate in XL³ cabinets and enclosures
MCCBs for switching, control isolation and protection of low voltage electrical lines
Supplied with fixing screws cage terminals 70 mm² max. (flexible cable) or 95 mm² max. rigid cable with accessories
Can be fitted with DPX³ 160 and 250 common auxiliares and accessories (p. 134)
Conform to IEC 60947-2

Pack	Cat.Nos		MCCBs - fixed version	
			Thermal adjustable from 0,8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)	
			Breaking capacity Icu 16 kA (400 V~)	
		In (A)		
	3P	4P		
1	4 200 00	4 200 10	16	
1	4 200 01	4 200 11	25	
1	4 200 02	4 200 12	40	
1	4 200 03	4 200 13	63	
1	4 200 04	4 200 14	80	
1	4 200 05	4 200 15	100	
1	4 200 06	4 200 16	125	
1	4 200 07	4 200 17	160	
			Breaking capacity Icu 25 kA (400 V~)	
1	4 200 40	4 200 50	16	
1	4 200 41	4 200 51	25	
1	4 200 42	4 200 52	40	
1	4 200 43	4 200 53	63	
1	4 200 44	4 200 54	80	
1	4 200 45	4 200 55	100	
1	4 200 46	4 200 56	125	
1	4 200 47	4 200 57	160	
			Breaking capacity Icu 36 kA (400 V~)	
1	4 200 80	4 200 90	16	
1	4 200 81	4 200 91	25	
1	4 200 82	4 200 92	40	
1	4 200 83	4 200 93	63	
1	4 200 84	4 200 94	80	
1	4 200 85	4 200 95	100	
1	4 200 86	4 200 96	125	
1	4 200 87	4 200 97	160	
			Breaking capacity Icu 50 kA (400 V~)	
1	4 201 20	4 201 30	16	
1	4 201 21	4 201 31	25	
1	4 201 22	4 201 32	40	
1	4 201 23	4 201 33	63	
1	4 201 24	4 201 34	80	
1	4 201 25	4 201 35	100	
1	4 201 26	4 201 36	125	
1	4 201 27	4 201 37	160	

Pack	Cat.Nos		MCCBs with electronic earth leakage module - fixed version	
			Thermal adjustable from 0,8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A) Equipped with earth leakage module with LCD screen Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0 s)	
			Breaking capacity Icu 16 kA (400 V~)	
		In (A)		
		4P		
1	4 200 30	16		
1	4 200 31	25		
1	4 200 32	40		
1	4 200 33	63		
1	4 200 34	80		
1	4 200 35	100		
1	4 200 36	125		
1	4 200 37	160		
			Breaking capacity Icu 25 kA (400 V~)	
1	4 200 70	16		
1	4 200 71	25		
1	4 200 72	40		
1	4 200 73	63		
1	4 200 74	80		
1	4 200 75	100		
1	4 200 76	125		
1	4 200 77	160		
			Breaking capacity Icu 36 kA (400 V~)	
1	4 201 10	16		
1	4 201 11	25		
1	4 201 12	40		
1	4 201 13	63		
1	4 201 14	80		
1	4 201 15	100		
1	4 201 16	125		
1	4 201 17	160		
			Breaking capacity Icu 50 kA (400 V~)	
1	4 201 50	16		
1	4 201 51	25		
1	4 201 52	40		
1	4 201 53	63		
1	4 201 54	80		
1	4 201 55	100		
1	4 201 56	125		
1	4 201 57	160		

See the video

