



QuickFlex



SCHUKO socket-outlet with hinged lid, IP44

16 A, AC 250 V, DIN 49440

Integrated protection against accidental contact as per VDE 0620 Part 1 (child protection).

Features:

- Frontal retrofitting of QuickFlex additional modules with no disassembling of the socket-outlet.
- Quick-fastening screws for securing of claws.
- Flush-mounted claws with return springs.
- High-gloss galvanised retaining ring insulated to the claw.

With claw and screw fixing.

With plug-in terminals.

■ **Contents:** Socket-outlet with sealing ring.

Version	Art. no.	PU	PG	Info
---------	----------	----	----	------

▶ Thermoplastic brilliant

white, glossy	MEG2314-0344	1/50	2.1	new
polar white, glossy	MEG2314-0319	1/50	2.1	new
active white, glossy	MEG2314-0325	1/50	2.1	new

▶ Thermoplastic classy matt

white	MEG2314-0444	1/50	2.1	new
polar white	MEG2314-0419	1/50	2.1	new
anthracite	MEG2314-0414	1/50	2.1	new
aluminium	MEG2314-0460	1/50	2.1	new

■ **Duroplastic, highly scratch-resistant: With this article, use thermoplastic brilliant**



SCHUKO socket-outlet insert with hinged lid IP44

16 A, AC 250 V, DIN 49440

Integrated protection against accidental contact as per VDE 0620 Part 1 (child protection).

With claw and screw fixing.

With plug-in terminals.

Type of protection: IP 44 splash-proof

■ **Contents:** Socket-outlet with sealing ring.

Version	Art. no.	PU	PG	Info
---------	----------	----	----	------

▶ Thermoplastic brilliant

white, glossy	238444	1/50	2.1	disc.
polar white, glossy	238419	1/50	2.1	disc.
active white, glossy	238425	1/50	2.1	disc.

▶ Thermoplastic classy matt

white	236644	1/50	2.1	disc.
polar white	236619	1/50	2.1	disc.
anthracite	236614	1/50	2.1	disc.
aluminium	236660	1/50	2.1	disc.

■ **Duroplastic, highly scratch-resistant: With this article, use thermoplastic brilliant**



QuickFlex



SCHUKO socket-outlet with hinged lid, lockable with various locks

16 A, AC 250 V, DIN 49440

Integrated protection against accidental contact as per VDE 0620 Part 1 (child protection).

Features:

- Frontal retrofitting of QuickFlex additional modules with no disassembling of the socket-outlet.
- Quick-fastening screws for securing of claws.
- Flush-mounted claws with return springs.
- High-gloss galvanised retaining ring insulated to the claw.

With claw and screw fixing.

With plug-in terminals.

Version	Art. no.	PU	PG	Info
---------	----------	----	----	------

▶ Thermoplastic brilliant

white, glossy	MEG2315-0344	1/40	1	new
polar white, glossy	MEG2315-0319	1/40	1	new
active white, glossy	MEG2315-0325	1/40	1	new

▶ Thermoplastic classy matt

white	MEG2315-0444	1/40	1	new
polar white	MEG2315-0419	1/40	1	new
anthracite	MEG2315-0414	1/40	1.1	new
aluminium	MEG2315-0460	1/40	1.1	new

■ **Duroplastic, highly scratch-resistant: With this article, use thermoplastic brilliant**



QuickFlex



SCHUKO socket-outlet with hinged lid and labelling field

16 A, AC 250 V, DIN 49440

Integrated protection against accidental contact as per VDE 0620 Part 1 (child protection).

Features:

- Frontal retrofitting of QuickFlex additional modules with no disassembling of the socket-outlet.
- Quick-fastening screws for securing of claws.
- Flush-mounted claws with return springs.
- High-gloss galvanised retaining ring insulated to the claw.

With claw and screw fixing.

With plug-in terminals.

■ **Accessories:** Large labelling field with touch contrast symbol for rockers and socket-outlets with labelling field, art. no. 434791/92/93/94.

Version	Art. no.	PU	PG	Info
---------	----------	----	----	------

▶ Thermoplastic brilliant

white, glossy	MEG2312-0344	10/60	1	new
polar white, glossy	MEG2312-0319	10/60	1	new
active white, glossy	MEG2312-0325	10/60	1	new

▶ Thermoplastic classy matt

white	MEG2312-0444	10/60	1	new
polar white	MEG2312-0419	10/60	1	new
anthracite	MEG2312-0414	10/60	1.1	new
aluminium	MEG2312-0460	10/60	1.1	new

■ **Duroplastic, highly scratch-resistant: With this article, use thermoplastic brilliant**