

Isolating switches RX³

from 40 A to 80 A



RCCBs RX³

residual current circuit breakers from 25 A to 63 A - AC and A types




4 193 24



4 193 28




4 193 32



4 020 25



4 020 70



Dimensions [see e-catalogue](#)

Conform to IEC 60947-3

Grey handle

AC 22 A

Compatible with prong-type and fork type supply busbars

Do not accept auxiliaries

Pack Cat.Nos Isolating switches

Pack	Cat.Nos	Isolating switches		
		2P - 400 V~		
		Nominal rating In (A)		Number of modules
6	4 193 24	40		2
6	4 193 25	63		2
6	4 193 26	80		2
		3P - 400 V~		
1	4 193 27	40		3
1	4 193 28	63		3
1	4 193 29	80		3
		4P - 400 V~		
1	4 193 30	40		4
1	4 193 31	63		4
1	4 193 32	80		4



Dimensions [see e-catalogue](#)

Conform to IEC 61008-1

• AC type : detect AC component faults

• A type : detect AC and DC component faults

Compatible with prong-type and fork type supply busbars

Do not accept auxiliaries

Pack Cat.Nos 2-pole - 230 V~

Pack	Cat.Nos	2-pole - 230 V~		
		AC type		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 24	30	25	2
1	4 020 25	30	40	2
1	4 020 26	30	63	2
1	4 020 27	30	80	2
1	4 020 28	100	25	2
1	4 020 29	100	40	2
1	4 020 30	100	63	2
1	4 020 32	300	25	2
1	4 020 33	300	40	2
1	4 020 34	300	63	2
		A type		
1	4 020 36	30	25	2
1	4 020 37	30	40	2
1	4 020 38	30	63	2
		4-pole - 400 V~ neutral on right-hand side		
		AC type		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 62	30	25	4
1	4 020 63	30	40	4
1	4 020 64	30	63	4
1	4 020 66	100	25	4
1	4 020 67	100	40	4
1	4 020 68	100	63	4
1	4 020 70	300	25	4
1	4 020 71	300	40	4
1	4 020 72	300	63	4
		A type		
1	4 020 74	30	25	4
1	4 020 75	30	40	4
1	4 020 76	30	63	4



For detailed dimensions,
[see e-catalogue](#)

