

# Polyester wall-mounting enclosures

## Polyester wall-mounting enclosures IP66



Class II












External dimensions			References of wall-mounting enclosures with door							
Height (mm)	Width (mm)	Depth (mm)	Plain	Transparent	Plain	Transparent	Plain	Transparent	Plain	Transparent
308	255	160	-	-	NSYPLM3025G	NSYPLM3025TG	-	-	-	-
310	215	160	NSYPLM32G	NSYPLM32TG	-	-	-	-	-	-
430	330	200	-	-	-	-	NSYPLM43G	NSYPLM43TG	NSYPLM43VG	NSYPLM43TVG
530	430	200	-	-	-	-	NSYPLM54G	NSYPLM54TG	NSYPLM54VG	NSYPLM54TVG
647	436	250	-	-	-	-	NSYPLM64G	NSYPLM64TG	NSYPLM64VG	NSYPLM64TVG
747	536	300	-	-	-	-	NSYPLM75G	NSYPLM75TG	NSYPLM75VG	NSYPLM75TVG
847	636	300	-	-	-	-	NSYPLM86G	NSYPLM86TG	NSYPLM86VG	NSYPLM86TVG
1056	852	350	-	-	-	-	NSYPLM108G	NSYPLM108TG	-	-
Details			see page 189							

# Polyester wall-mounting enclosures

Selection guide

## Mounting accessories

			Metallic mounting plates				Insulating mounting plates		Modular distribution chassis	Step slides	Symmetrical DIN rail
											
Dimensions			Plain	Silkscreened	Micro-perforated	Telequick	Bakelite	Polyester			
Height (mm)	Width (mm)	Depth (mm)									
310	215	160	NSYMM32	-	-	NSYMR32	NSYMB32	NSYMPP32	-	-	NSYCS200PLM
308	255	160	NSYMM3025	-	-	NSYMR3025	NSYMB3025	NSYMPP3025	NSYDLPLM18G	-	-
430	330	200	NSYMM43	NSYMS43	NSYMF43	NSYMR43	NSYMB43	NSYMPP43	NSYDLA24G	NSYDPLM200	NSYCS300PLM
530	430	200	NSYMM54	NSYMS54	NSYMF54	NSYMR54	NSYMB54	NSYMPP54	NSYDLA48G	NSYDPLM200	NSYCS400PLM
647	436	250	NSYMM64	NSYMS64	NSYMF64	NSYMR64	NSYMB64	NSYMPP64	NSYDLA48PG	NSYDPLM250	NSYCS400PLM
747	536	300	NSYMM75	NSYMS75	NSYMF75	NSYMR75	NSYMB75	NSYMPP75	NSYDLA66G and NSYDLA88G	NSYDPLM300	NSYCS500PLM
847	636	300	NSYMM86	NSYMS86	NSYMF86	NSYMR86	NSYMB86	NSYMPP86	NSYDLA84G and NSYDLA112G	NSYDPLM300	NSYCS600PLM
1056	852	350	NSYMM108	-	NSYMF108	NSYMR108	NSYMB108	NSYMPP108	NSYDLA234G	NSYDPLM350	NSYCS800PLM
Details			see page 240				see page 241		see page 194	see page 198	

## Main accessories

											
Dimensions			Fixing lugs	Postfixing device	Floormounting pillar	Coupling frame	Cablegland plate	Internal door	Blanking plates	Plinth ZM RAL 7032	
Height (mm)	Width (mm)	Depth (mm)									
310	215	160	NSYPFPLM32G	-	-	-	-	-	NSYCEPLMAG	-	
308	255	160	NSYPFPLMG	-	-	-	-	NSYPA3025PLMG	-	-	
430	330	200	NSYPFPLMG	NSYSFP300	-	-	-	NSYPAP43G	NSYCEPLMBG	-	
530	430	200	NSYPFPLMG	NSYSFP400	NSYSFSPLMG	-	-	NSYPAP54G	NSYCEPLMBG	-	
647	436	250	NSYPFPLMG	NSYSFP400	NSYSFSPLMG	-	-	NSYPAP64G	NSYCEPLMCG	-	
747	536	300	NSYPFPLMG	NSYSFP500	-	NSYBUPLMG	NSYTLA4420G	NSYPAP75G	NSYCEPLMCG	NSYZM253G	
847	636	300	NSYPFPLMG	NSYSFP600	-	NSYBUPLMG	NSYTLA4420G	NSYPAP86G	NSYCEPLMCG	NSYZM263G	
1056	852	350	NSYPFPLMG	-	-	NSYBU108PLMG	NSYTLA6420G	NSYPAP108G	-	NSYZM283G	
Details			see page 192			see page 198		see page 193	see page 192	see page 191	

Water drain plug: Page 199  
 Rail-fixing nuts: Page 198  
 Ventilation louvre: Page 199

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.